AMENDMENTS TO THE CLAIMS

(currently amended) A floor-treatment floor-cleaning machine operable along a working 1. direction comprising: with

an undercarriage (1),

From-15 RECP

Jan-28-2004 05:07pm

at least one positionally-fixed floor-cleaning unit, and

at least one positionally adjustable floor treatment floor-cleaning unit (11), which is attached to the undercarriage (1) in such a way that it can pivot said at least one positionally adjustable floor-cleaning unit pivots around a substantially vertical axis (20, 29) in order to vary the working width a working width of said at least one positionally adjustable floor-cleaning unit, characterized in that the

wherein the at least one positionally adjustable floor-treatment floor-cleaning unit (11) can be pivoted in two directions (B, C) from its position corresponding to the maximum a maximum working width in order to reduce the working width, and

wherein the at least one positionally adjustable floor-cleaning unit is attached to the undercarriage in a manner that allows to vary its inclination relative to a horizontal plane.

- (currently amended) A floor-treatment floor-cleaning machine according to claim 1, 2. eharacterized in that wherein the at least one positionally adjustable floor-treatment floorcleaning unit (11) is attached to the undercarriage (1) in such a way that it can be displaced linearly (D) in addition to its pivoting capability (B, C) in two directions.
- (currently amended) A floor-treatment floor-cleaning machine according to claim 2, 3. eharucterized in that wherein the linear displacement (D) of the at least one positionally adjustable floor treatment floor-cleaning unit (11) takes place perpendicular to the working direction-(A).
- (currently amended) A floor-treatment floor-cleaning machine according to one of claims 4. 2 or 3, eharacterized in that further comprising a working drive unit is provided for linear

09/889,365 11176540.01 displacement (D) of the at least one positionally adjustable floor treatment floor-cleaning unit (11).

- 5. (currently amended) A floor-treatment floor-cleaning machine according to claim 4, eharacterized in that there is provided, in the front part thereof, further comprising a touch contact provided in a front part of said machine which acts on thea controller of the drive unit-for the at least one positionally adjustable floor-treatment unit.
- 6. (currently amended) A floor-treatmentfloor-cleaning machine according to claim 1, eharacterized in that wherein the at least one positionally adjustable floor-treatmentfloor-cleaning unit (11) is attached to the a front rim of the undercarriage (1) relative to the main working direction-(A).
- 7. (currently amended) A floor-treatment floor-cleaning machine according to claim 1, characterized in that wherein the at least one positionally adjustable floor-treatment floor-cleaning unit (11) is held in its position corresponding to and biased toward the maximum working width by means of a spring device that applies an initial force.
- 8. (currently amended) A floor treatment floor-cleaning machine according to claim 1, eharacterized in that wherein the at least one positionally adjustable floor-treatment floor-cleaning unit (11) is attached to the undercarriage (1) in such a way that it can pivots around a horizontal axis (14) in order to vary its inclination.
- 9. (canceled)
- 10. (currently amended) A floor-treatment floor-cleaning machine according to elaim 9 claim 1, characterized in that wherein at least one positionally adjustable floor treatment floor-cleaning unit further comprises a revolving endless sweeping belt-(15).

09/889,365 11176540.01

- 11. (currently amended) A floor-treatment floor-cleaning machine according to claim 10, characterized in that the wherein a direction of revolution (E) of the revolving endless sweeping belt (15) is reversible.
- 12. (currently amended) A floor-treatment floor-cleaning machine according to claim 11, eharacterized in that wherein the direction of revolution (E) of the endless sweeping belt (15) reverses automatically upon reversal of the working direction.
- 13. (currently amended) A floor-treatment floor-cleaning machine according to elaim 9 claim 1, eharacterized in that wherein the positionally adjustable floor-treatment floor-cleaning unit comprises a rotary brush (24), which is driven in rotation (F) and whose having a bristle array (27) is disposed in the form of a helical coil.

09/889,365 11176540.01